NOTICE IS HEREBY GIVEN THAT THE CHRISTIAN COUNTY PLANNING AND ZONING COMMISSION will hold a public hearing on Monday, October 20, 2025, at 6:00 p.m. at 1106 W. Jackson Street, Ozark, Missouri. Unless tabled or withdrawn, this case will be heard by the Christian County Board of Adjustment at 9:00 a.m. on Tuesday, November 4, 2025. Information may be examined at the Planning and Development Office, 1106 W. Jackson Street, Ozark, Missouri, between the hours of 8:00 a.m. and 4:30 p.m., Monday through Friday (417) 581-7242.

CASE NUMBER 2025-0235

APPLICANT: BRADLEY C. & DENISE L. ANDERSON / JMT EXCAVATING

PETITION: PROPOSED CONDITIONAL USE PERMIT FOR SURFACE MINING WITHIN PARCEL # 19-0.1-01-0-0-11.000

LOCATION: 652 RIVERDALE ROAD, NIXA, MISSOURI

LEGAL:

TRACT I: THAT CERTAIN PARCEL OR TRACT OF LAND BEING A PART OF SECTION ONE (1) AND SECTION TWO (2), TOWNSHIP TWENTY-SIX (26) NORTH, RANGE TWENTY-TWO (22) WEST, CHRISTIAN COUNTY, MISSOURI, BEING DESCRIBED AS FOLLOWS:

COMMENCING AT AN EXISTING STONE AT THE NORTHWEST CORNER OF THE EAST HALF (E½) OF LOT TWO (2) OF THE NORTHWEST QUARTER (NW½) OF SAID SECTION TWO (2); THENCE: SOUTH 01°45′51" FAST, ALONG THE WEST LINE OF SAID EAST HALF (E½), A DISTANCE OF 1461.74 FEET TO AN EXISTING STONE; THENCE SOUTH 80°58′31" EAST, A DISTANCE OF 1322.29 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "TODD"; THENCE SOUTH 01°37′18" WEST, A DISTANCE OF 1089.19 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383"; THENCE SOUTH 01°37′18" WEST, A DISTANCE OF 1089.19 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383"; THENCE SOUTH 01°37′39" WEST, A DISTANCE OF 228.44 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383"; THENCE SOUTH 01°37′39" WEST, A DISTANCE OF 28.44 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "BUCHANAN"; THENCE SOUTH 12°44′46" EAST, A DISTANCE OF 747.25 FEET TO AN EXISTING 1/2" IRON PIN WITH A CAP STAMPED "BUCHANAN", SAID POINT ALSO BEING ON THE NORTH RIGHT-OF-WAY LINE OF SAID RIVERDALE ROAD; THENCE ALONG SAID NORTH RIGHT-OF-WAY LINE, ALONG A CURVE TO THE RIGHT, SAID CURVE HAVING A RADIUS 471.80 FEET, AN ARC DISTANCE OF 216.02 FEET, A CENTRAL ANGLE OF 26°14′03", ALONG A CHORD BEARING SOUTH 133°51′00" WEST, A CHORD DISTANCE OF 214.14 FEET TO AN EXISTING 1/2" IRON PIN WITH A CAP STAMPED "BUCHANAN"; THENCE SOUTH 10°38′23" WEST, A DISTANCE OF 40.00 FEET TO A POINT ON THE SOUTH RIGHT-OF-WAY LINE OF SAID RIVERDALE ROAD AND THE POINT OF BEGINNING; THENCE ALONG SAID SOUTH RIGHT-OF-WAY LINE FOR THE FOLLOWING

THENCE ALONG SAID SOUTH RIGHT-OF-WAY LINE FOR THE FOLLOWING TWELVE (12) DESCRIBED COURSES:

THENCE, ALONG A CURVE TO THE LEFT, SAID CURVE HAVING A RADIUS OF 511.80 FEET, AN ARC DISTANCE OF 230.55 FEET, A CENTRAL ANGLE OF 25°48'36", ALONG A CHORD BEARING NORTH 83°38'31" EAST, A CHORD DISTANCE OF 228.61 FEET; THENCE NORTH 67°22'35" EAST, A DISTANCE OF 485.18 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383"; THENCE NORTH 67°20'36" EAST, A DISTANCE OF 134.20 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383" AND A POINT OF

24°44'40", ALONG A CHORD BEARING NORTH 82°32'29" EAST, A CHORD DISTANCE OF 162.95 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383"; THENCE NORTH 70°29'58" EAST, A DISTANCE OF 127.28 FEET TO AN EXISTING HIGHWAY RIGHT-OF-WAY MARKER ON THE WEST RIGHT-OF-WAY LINE OF MISSOURI STATE HIGHWAY 160; THENCE ALONG SAID WEST RIGHT-OF-WAY LINE FOR THE FOLLOWING EIGHT (8) DESCRIBED COURSES:

THENCE NORTH 81°40'36" EAST, A DISTANCE OF 103.88 FEET TO AN EXISTING HIGHWAY RIGHT-OF-WAY MARKER; THENCE NORTH 70°37'40" EAST, A DISTANCE OF 120.57 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383"; THENCE SOUTH 54°13'53" EAST, A DISTANCE OF 67.58 FEET.

57.38 FEEL;
THENCE SOUTH 14°07'51" EAST, A DISTANCE OF 232.74 FEET TO AN
EXISTING HIGHWAY RIGHT-OF-WAY MARKER; THENCE SOUTH 09°40'12"
EAST, A DISTANCE OF 203.96 FEET TO AN EXISTING HIGHWAY
RIGHT-OF-WAY MARKER; THENCE SOUTH 66°11'47" EAST, A DISTANCE OF
57.58 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383";
THENCE SOUTH 28°40'52" EAST, A DISTANCE OF 539.65 FEET TO AN
EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383"; THENCE SOUTH
48°56'09" EAST, A DISTANCE OF 50.96 FEET TO A POINT ON THE NORTH
BANK OF THE FINLEY RIVER;

THENCE ALONG SAID NORTH BANK FOR THE FOLLOWING FOURTEEN (14) DESCRIBED COURSES:

THENCE SOUTH 00°46'42" WEST, A DISTANCE OF 49.12 FEET; THENCE SOUTH 04°37'41" WEST, A DISTANCE OF 190.91 FEET; THENCE SOUTH 53°07'08" WEST, A DISTANCE OF 47.33 FEET; THENCE SOUTH 72°51' 38" WEST, A DISTANCE OF 415.71 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383"; THENCE SOUTH 53°42'14" WEST, A DISTANCE OF 334.53 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383"; THENCE SOUTH 46°45'38" WEST, A DISTANCE OF 289.86 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383"; THENCE SOUTH 40°25'58" WEST, A DISTANCE OF 262.65 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383"; THENCE SOUTH 36°27'54" WEST, A DISTANCE OF 41.24 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383"; THENCE SOUTH 36°27'54" WEST, A DISTANCE OF 382.51 FEET; THENCE SOUTH 44°37'05" WEST, A DISTANCE OF 126.73 FEET; THENCE NORTH 89°32'14" WEST, A DISTANCE OF 265.94 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383"; THENCE SOUTH 67°52'08" WEST, A DISTANCE OF 164.73 FEET; TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383"; THENCE SOUTH 67°52'08" WEST, A DISTANCE OF 164.73 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383"; THENCE SOUTH 67°52'08" WEST, A DISTANCE OF 164.73 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383"; THENCE SOUTH 67°52'08" WEST, A DISTANCE OF 218.22

CURVATURE TO THE LEFT; THENCE ALONG SAID CURVE TO THE LEFT, SAID CURVE HAVING A RADIUS OF 620.00 FEET, AN ARC DISTANCE OF 214.79 FEET, A CENTRAL ANGLE OF 19°50'59", ALONG A CHORD BEARING NORTH 59°38'56" EAST, A CHORD DISTANCE OF 213.72 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383"; THENCE NORTH 49°51'45" EAST, A DISTANCE OF 91.50 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383" AND A POINT OF CURVATURE TO THE LEFT; THENCE ALONG SAID CURVE TO THE LEFT, SAID CURVE HAVING A RADIUS OF 470.00 FEET, AN ARC DISTANCE OF 242.88 FEET, A CENTRAL ANGLE OF 29°36'32", ALONG A CHORD BEARING NORTH 34°52'46" EAST, A CHORD DISTANCE OF 240.19 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383"; THENCE NORTH 20°04'58" EAST, A DISTANCE OF 233.01 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383" AND A POINT OF CURVATURE TO THE LEFT; THENCE ALONG SAID CURVE TO THE LEFT, SAID CURVE HAVING A RADIUS OF 340.00 FEET, AN ARC DISTANCE OF 173.95 FEET, A CENTRAL ANGLE OF 29°18'51", ALONG A CHORD BEARING NORTH 05°13'51" EAST, A CHORD DISTANCE OF 172.06 FEET TO A SET 1/2" IRON PIN WITH A CAP STAMPED "WLS LC 370"; THENCE NORTH 27°39'16" EAST, A DISTANCE OF 73.62 FEET TO A SET 1/2" IRON PIN STAMPED "WLS LC 370; THENCE NORTH 34°28'05" EAST, A DISTANCE OF 18.54 FEET TO AN EXISTING 1/2" IRON PIN WITH A CAP STAMPED "TODD"; THENCE SOUTH 40°57'47" EAST, A DISTANCE OF 233.41 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "TODD"; THENCE NORTH 45°13'14" EAST, A DISTANCE OF 414.54 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383"; THENCE NORTH 24°09'56" EAST, A DISTANCE OF 228.79 FEET TO AN EXISTING 1/2" IRON PIN WITH A CAP STAMPED "TODD"; THENCE NORTH 27°27'44" WEST, A DISTANCE OF 114.38 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383" TO SAID POINT ALSO BEING ON THE AFORESAID SOUTH RIGHT-OF-WAY LINE OF RIVERDALE ROAD; THENCE, ALONG SAID SOUTH RIGHT-OF-WAY LINE FOR THE FOLLOWING FIVE (5) DESCRIBED COURSES:

THENCE NORTH 56°05'09" EAST, A DISTANCE OF 570.48 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383" AND A POINT OF CURVATURE TO THE RIGHT; THENCE ALONG SAID CURVE TO THE RIGHT, SAID CURVE HAVING A RADIUS OF 81.14 FEET, AN ARC DISTANCE OF 54.72 FEET, A CENTRAL ANGLE OF 38°38'24", ALONG A CHORD BEARING NORTH 75°25'55" EAST, A CHORD DISTANCE OF 53.69 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383"; THENCE SOUTH 85°15'18" EAST, A DISTANCE OF 314.86 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383" AND A POINT OF CURVATURE TO THE LEFT; THENCE ALONG SAID CURVE TO THE LEFT, SAID CURVE HAVING A RADIUS OF 380.26 FEET, AN ARC DISTANCE OF 164.22 FEET, A CENTRAL ANGLE OF

PEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383"; THENCE SOUTH 70°38'43" WEST, A DISTANCE OF 66.54 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383"; THENCE NORTH 26°05'41" WEST, A DISTANCE OF 161.00 FEET; THENCE NORTH 89°23'48" WEST, A DISTANCE OF 490.94 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383"; THENCE NORTH 89°06'02" WEST, A DISTANCE OF 671.66 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "TODD"; THENCE NORTH 01°39'46 "EAST, A DISTANCE OF 363.46 FEET TO AN EXISTING 5/8" IRON PIN WITH A CAP STAMPED "LC 383"; THENCE NORTH 01°38'23" EAST, A DISTANCE OF 342.92 FEET TO THE POINT OF BEGINNING.

EXCEPTING THAT PORTION DEEDED AND USED FOR GLENN CEMETERY, BEING DESCRIBED AS FOLLOWS:

BEING DESCRIBED AS FOLLOWS:

COMMENCING AT AN EXISTING STONE AT THE NORTHWEST CORNER OF THE EAST HALF (E½) OF LOT TWO (2) OF THE NORTHWEST QUARTER (NW¼) OF SAID SECTION TWO (2); THENCE SOUTH 01°45′51″ EAST, ALONG THE WEST LINE OF SAID EAST HALF (E½), A DISTANCE OF 1461.74 FEET TO AN EXISTING STONE; THENCE SOUTH 89°58′31″ EAST, A DISTANCE OF 1322.29 FEET TO AN EXISTING 5/8″ IRON PIN WITH A CAP STAMPED "TODD"; THENCE SOUTH 01°37′18″ WEST, A DISTANCE OF 1089.19 FEET TO AN EXISTING 5/8″ IRON PIN WITH A CAP STAMPED "LC 383″; THENCE SOUTH 88°22′35″ EAST, A DISTANCE OF 1101.31 FEET TO AN EXISTING 5/8″ IRON PIN WITH A CAP STAMPED "LC 383″; THENCE SOUTH 88°22′35″ EAST, A DISTANCE OF 101.31 FEET TO AN EXISTING 5/8″ IRON PIN WITH A CAP STAMPED "LC 383″; THENCE SOUTH 20°52′52″ EAST, A DISTANCE OF 39.84 FEET AN EXISTING 5/8″ IRON PIN WITH A CAP STAMPED "LC 383″ ON THE SOUTH RIGHT-OP-WAY LINE OF RIVERDALE ROAD;
THENCE SOUTH 82°13′13″ EAST, A DISTANCE OF 673.38 FEET TO AN EXISTING 1/2″ IRON PIN WITH A CAP STAMPED "TODD", AND THE POINT OF BEGINNING; THENCE NORTH 52°21′50″ EAST, A DISTANCE OF 405.53 FEET TO AN EXISTING 570NE; THENCE SOUTH 47°00′00″ EAST, A DISTANCE OF 103.93 FEET, THENCE SOUTH 02°38′39″ WEST, A DISTANCE OF 159.21 FEET TO AN EXISTING 50NE; THENCE SOUTH 40°00′00″ EAST, A DISTANCE OF 114.01 FEET TO AN EXISTING 1/2″ IRON PIN WITH A CAP STAMPED "TODD"; THENCE ON THE SCOUTH 20°07′18″ WEST, A DISTANCE OF 114.01 FEET TO AN EXISTING 1/2″ IRON PIN WITH A CAP STAMPED "TODD"; THENCE NORTH 20°31′30″ WEST, A DISTANCE OF 23.65 FEET TO AN EXISTING 1/2″ IRON PIN WITH A CAP STAMPED "TODD"; THENCE NORTH 37°31′15″ WEST, A DISTANCE OF 723.65 FEET TO AN EXISTING 1/2″ IRON PIN WITH A CAP STAMPED "TODD"; THENCE NORTH 37°31′15″ WEST, A DISTANCE OF 100D"; THENCE NORTH 37°31′15″ WEST, A DISTANCE OF 100D"; THENCE NORTH 37°31′15″ WEST, A DISTANCE OF 23.65 FEET TO AN

Scott Hayes, Executive Secretary **Christian County Planning and Zoning Commission**

